

Short handle lock SIS044G

Specifications

- External dimensions (height x width x depth): 160 x 82 x 135 mm.
- Finish: Glossy graphite effect.
- Glass: 8, 10, 12 mm.
- Lock cylinder on both sides: Yes.
- Recommended use: Indoor/outdoor.

Characteristics

- Clamp plates made of an aluminium alloy coated with epoxy paint.
- Glass clamping gaskets made of PE.
- A2 stainless steel screws.
- Frontal plates made of stainless steel.
- AISI 316 stainless steel covers.
- Euro cylinder multi point lock.
- Key activated reversible latch bolt.
- Latch bolt that moves 10 mm with one turn of the key.
- Dead bolt that moves 20 mm by turning the key twice, anti-cut treatment.
- Cylinder 40 mm from edge.
- 5 sets of keys.

Considerations

- The door must be 100 mm wider than the other panels.
- When using an L profile, the door must be 110 mm wider than the other panels.
- If used on a Sliding Door, the panel must be 130 mm wider than the other panels.

Personalisation

- Personalised with CLAROFLEX® logo.
- Bespoke logo engraved on covers. Minimum order: 5 locks.

Prices

SIS044G/8 167 €

SIS044G/10 165 €

SIS044G/12 180 €

