

Long handle lock SIS045

Specifications

- External dimensions (height x width x depth): $160 \times 155 \times 140$ mm.
- Finishes: Polished or satin stainless steel.
- Glass: 8, 10, 12 mm.
- Lock cylinder on both sides: Yes.
- Recomended use: Indoor/outdoor.

Characteristics

- Clamp plates made of an aluminium alloy coated with epoxy paint.
- Glass clamping gaskets made of PE.
- A2 stainless steel screws.
- Stainless steel handles.
- Frontal plates made of stainless steel.
- AISI 316 stainless steel covers.
- Euro cylinder multi point lock.
- Key activated reversible latch bolt.
- Latch bolt that moves 10 mm with one turn of the key.
- Dead bolt that moves 20 mm by turning the key twice, anti-cut treatment.
- Cylinder 40 mm from edge.
- 5 sets of keys.

Considerations

- The door must be 190 mm wider than the other panels.
- When using an L profile, the door must be 200 mm wider than the other panels.
- If used on a Sliding Door, the panel must be 220 mm wider than the other panels.

Personalisation

Personalised with CLAROFLEX[®] logo.

Prices

SIS045/8 (Polished) 135,9 € SIS045M/8 (Satin) 149,3 €

SIS045/10 (Polished) 133,9 € SIS045M/10 (Satin) 147,3 € SIS045/12 (Polished) 147,3 €

Bespoke logo engraved on covers.

Minimum order: 5 locks.

A







