

Lock without handle SIS074

Specifications

- External dimensions (height x width x depth): 160 x 82 x 65 mm.
- Finishes: Polished or satin stainless steel.
- Glass: 8, 10, 12 mm.
- Lock cylinder on both sides: Yes.
- Recommended use: Indoor/outdoor.

Characteristics

- Clamp plates made of an aluminium alloy coated with epoxy paint.
- Glass clamping gaskets made of PE.
- A2 stainless steel screws.
- Frontal plates made of stainless steel.
- AISI 316 stainless steel covers.
- Euro cylinder multi point lock.
- Key activated reversible latch bolt.
- Dead bolt that moves 20 mm by turning the key twice, anti-cut treatment.
- Cylinder 40 mm from edge.
- 5 sets of keys.

Considerations

- The door must be 80 mm wider than the other panels.
- When using an L profile, the door must be 90 mm wider than the other panels.
- If used on a Sliding Door, the panel must be 110 mm wider than the other panels.

Personalisation

- Personalised with CLAROFLEX® logo.
- Bespoke logo engraved on covers. Minimum order: 5 locks.



Prices

SIS074/8 (Polished)	114,5 €	SIS074/10 (Polished)	112,5 €	SIS074/12 (Polished)	123,7 €
SIS074M/8 (Satin)	130,5 €	SIS074M/10 (Satin)	128,5 €	SIS074M/12 (Satin)	141,4 €

